

ATTACHMENT PLUG

CAT. NO. C14G2S

(REPRESENTS CAT. NO. C16G)

FIG. 1A (M93-26383)

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. Cat. No. C14G2S is similar to Cat. No. C14G except for the 2 slots in the shroud.

Cat. No. C16G is similar to Cat. No. C14G2S except it has one slot in the shroud. Refer to Ill. 1 for further details.

1. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Overall dimensions 2 in (50.8 mm) long, 1-1/8 in (28.6 mm) wide, 13/16 in (20.6 mm) high. Shroud min 5/64 in (1.98 mm) thick, 21/32 in (16.6 mm) high from face. Two slots in shroud 21/32 in (16.6 mm) long, 1/4 in wide.
2. Face - Recessed 21/32 in (16.6 mm) from body, overall dimensions 31/32 in (24.6 mm) by 21/32 in (16.6 mm).
3. Cord Entry - 9/16 in (14.2 mm) by 9/16 in (14.2 mm), by 13/16 in (20.6 mm) long.

4.

Flexible Cord - Listed Flexible (ZJCZ/7). See the following table for details.

Cord Size (AWG)	Cord Type	USL	CNL or CSA Certified
18	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO, SVT, SVTO, SVTOO	YES	YES
16	SJT, SJTO, SJTW, SJTOW, SJTOOW, SJTOO, SVT, SVTO, SVTOO	YES	YES

*

5. Blades - Folded from 0.037 in (0.94 mm) thick copper alloy stock, plating optional, overall length including electrical connections approx 1-1/32 in (26.2 mm).

Alternate - Line blade, No. 1409 and grounding blade, No. 1408, refer to Vol. 1C, Sec. 6 of this File for details.

6. Electrical Connection - Crimped to conductor, crimp length approx 3/16 in (4.7 mm).