

ATTACHMENT PLUG, CAT. NO. C8G

FIG. 1 (M98-01396)

1. Contacts - Feller, Cat. No. 8008, refer to Vol. 1C, Sec. **12** for further details.
2. Body - Molded of one of the plastic materials tabulated in Construction Details portion of report. Min 3/32 in (2.4 mm) thickness of molding material covers live parts, overall length 1-15/16 in (49.2 mm) including cord entry (not including premold, Item 6). Refer to Ill. 1 for further details.
3. Face - Overall dimensions 11/16 in (17.4 mm) by 11/32 in (8.7 mm), recessed 17/32 in (13.5 mm) from top of shroud.
4. Cord Entry - Overall dimensions 7/16 in (11.1 mm) dia by 3/4 in (19.1 mm) long.
5. Flexible Cord - Listed Flexible (ZJCZ/7). See the following table for details.

Cord Size (AWG)	Cord Type	USL	CNL or CSA Certified
*18	SVT, SVTO, SVTOO , SPT-2	YES	YES

6. Premold - Molded of Recognized Component Plastic (QMFZ2) Noryl GFN1, flame rating 94HB manufactured by Sabic Innovative Plastics BV. Overall dimensions 1-5/32 in (29.3 mm) long; 25/32 in (19.8 mm) wide; 7/16 in (11.1 mm) high. Refer to Ill. 2 for further details.
7. **Alternate Premold - Molded of Recognized Component Plastic (QMFZ2) material Polyamide 66 (PA 66), Type VAMPAMID 66 2526 V0(e) (f) by VAMP-TECH SPA (E140692). Refer to Ill. 3 for further details.**
8. Marking - (Not shown) Listee's name or trade name molded on body.